

Section 3 - Physical Data			
Boiling Point (F)	NA	Specific Gravity	NA
Vapor Pressure	NA	Percent Volatile by Volume	NA
Vapor Density	NA	Evaporation Rate	NA
Solubility in Water:		Slight (0.01 to 1.0%)	
Appearance and Odor:		Gray, plastic, flowable, granular mud and odorless.	

Section 4 - Fire and Explosion Hazard Data			
Flash Point (Method Used)	NA	Flammable Limits	NA
Extinguishing Media	NA	LeI	NA
Special Fire Fighting Procedures	NA	UeI	NA
Unusual Fire and Explosion Hazards	NA		

Section 5 - Health Hazard Data	
Threshold Limit Value	NA
Effects of Overexposure: Acute -- Wet plastic, unhardened concrete, can dry the skin and cause alkali burns (cement dermatitis). Chronic -- Hypersensitive individuals may develop an allergic dermatitis. Cement may contain trace amounts of chromium.	

Emergency First Aid Procedures:	
Eyes:	Irrigate with water. If irritation persists, contact a physician.
Skin:	Wash exposed areas with soap and water. If alkaline burn develops, see a physician.

Section 6 - Reactivity Data			
Stability	Unstable		Conditions to Avoid: NA
	Stable	X	Product hardens in 2 to 8 hours and is no longer hazardous
Incompatibility (Material to Avoid):		None	
Hazardous Decomposition Products:		None	
Hazardous Polymerization	May Occur		Conditions to Avoid: NA
	Will Not Occur	X	

Section 7 - Spill or Leak Procedures	
Steps to be Taken in Case Material is Released or Spilled: No hazard is created by a spill.	
Waste Disposal Method: Material can be retained until it hardens then it can be disposed of as common waste.	

Section 8 - Special Protection Information					
Respiratory Protection (Specity Type):			Not required		
Ventilation	Local Exhaust	NA	Special	NA	
	Mechanical (General)	NA		Other	NA
Protective Gloves: See Section 9			Eye Protection: See Section 9		
Other Protective Equipment: See Section 9					

Section 9 - Special Precautions	
Precautions to be Taken in Handling and Storing: Use barrier creams, gloves, boots, and clothing to protect the skin from contact with plastic concrete. Particularly avoid abrasion of the skin in contact with unhardened plastic concrete. Precautions must be observed because cement burns occur with little warning--little heat is sensed. Eye protection is not generally required except when placing methods cause splash then tight fitting goggles should be used.	
Other Precautions:	

NOTICE: Information contained herein is generic as to the hazards associated with different mixture designs.